

Mobil Delvac™ lubricant recommendations for Renault Trucks and light commercials



Mobil Delvac™: a comprehensive range of engine and gear oils you can trust

Mobil Delvac is one of the best-selling brands of heavy duty oil in the world with an extensive range of lubricants, greases and specialty products. A brand trusted by millions of truck owners, workshop managers and fleet professionals – including those using Renault trucks.

Our commitment to extensive on-going research and development ensures Mobil Delvac stays at the forefront of lubrication technology and meets and exceeds the demands of today's heavy duty trucks and light commercial vehicles.

Like Renault, we believe our customer's satisfaction and profitability is vital. Just as you depend on the efficiency, value and quality of your Renault truck, you can depend on the specially selected family of Mobil Delvac products to help in the battle to achieve optimum operational efficiency.

Your investment in a premium brand like Renault needs to be protected. Mobil Delvac protects as it performs. Mobil Delvac formulations use powerful additive technologies and high quality base oils which together help to resist oil degradation, reduce

engine wear and achieve long oil drain intervals. The goal is to help you to achieve long engine life.

Mobil Delvac offers an extensive 'bumper to bumper' range of high performance products for your commercial vehicle, which re formulated not only to meet key Renault specifications, but also a wide range of OEM and industry approvals offering outstanding performance and protection in some of the most demanding conditions.

Whether you are an owner operator, fleet owner or workshop manager, you can entrust your Renault commercial vehicle lubrication to Mobil Delvac.



Mobil Delvac™ Engine Oils

Specifications	Engine Oil
RLD-3	Mobil Delvac 1 LE 5W-30 Mobil Delvac MX ESP 10W-30 Mobil Delvac MX ESP 15W-40 Mobil Delvac XHP ESP 10W-40
RLD-2	Mobil Delvac 1 LE 5W-30 Mobil Delvac XHP ESP 10W-40 Mobil Delvac MX Extra 10W-40 Mobil Delvac MX 15W-40
RXD	Mobil Delvac 1 LE 5W-30 Mobil Delvac 1 5W-40 Mobil Delvac XHP ESP 10W-40 Mobil Delvac XHP Extra 10W-40
RGD	Mobil Delvac 1 LE 5W-30 Mobil Delvac XHP ESP 10W-40

Please refer to your specific OEM manual for full product recommendation listings and applicable oil drain intervals. Mobil Delvac products meet or exceed the requirements of those Renault Truck specifications.



Fuel economy potential

Low SAPS

Mobil Delvac 1™ LE 5W-30

Advanced engine and emission system protection

- Fully synthetic supreme performance low ash diesel engine oil
- Helps extend engine and emission system life, long drain capability and fuel economy potential
- Suitable for engines fitted with Diesel Particulate Filters



Mobil Delvac™ MX ESP 10W-30

Delivering performance beyond the boundaries of industry of API CJ-4 requirements

- Excellent pumpability helps engine protection at (cold temperature) start-up and provides fuel economy potential
- Provides excellent control of oil thickening due to soot build-up and TBN retention for long drain intervals
- Suitable for engines fitted with Diesel Particulate Filters



Mobil Delvac™ XHP ESP 10W-40

Advanced engine and emission system protection

- Synthetic extra high performance diesel engine oil engineered to provide lubrication to low emissions engines
- Designed using high performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention, and volatility control
- Suitable for engines fitted with Diesel Particulate Filters



Mobil Delvac™ MX 15W-40

For technically advanced modern engines

- Surpasses stringent engine test requirements
- Formulated to provide improved soot handling, wear and oxidation resistance
- Excellent lubrication of modern heavy-duty diesel engines, promoting long engine life



Mobil Delvac™ Gear Oils

Where the Differential requires the following	Mobil Products
Meets the Requirements of API GL-5 Synthetic. SAE 75W-90	Mobilube 1 SHC 75W-90 Mobil Delvac 1 Gear Oil 75W-90
Meets the Requirements of API GL-5 Synthetic. SAE 75W-140	Mobil Delvac 1 Gear Oil 75W-140
Meets the Requirements of API GL-5. SAE 80W-90	Mobilube S 80W-90 Mobilube HD-A Plus 80W-90 Mobilube HD 80W-90
Meets the Requirements of API GL-5. SAE 85W-140	Mobilube HD 85W-140

Where the Transmission requires the following	Mobil Products
API GL-4 quality level SAE 75W-90	Mobilube 1 SHC 75W-90
API GL-4 quality level SAE 75W-80 ZF TE-ML 02L approved	Mobil Delvac 1 Transmission Fluid 75W-80
API GL-4 quality level SAE 80W-90	Mobilube S 80W-90 Mobilube GX 80W-90
API GL-4 quality level SAE 80W	Mobilube GX-A 80W
GM Dexron III G quality level	Mobil Delvac 1 ATF Mobil ATF 320
GM Dexron II quality level	Mobil ATF 220

ExxonMobil quality level. Please refer to your specific OEM manual for full product recommendation listings and applicable oil drain intervals. Product information correct at the time of publication.

Mobilube 1 SHC™ 75W-90

Advanced synthetic technology for transmissions and rear axles

- Extended service capability in a wide range of applications
- Provides good thermal and oxidation stability, inherently high VI, extremely low pour point, excellent low temperature fluidity and fuel economy potential

Mobil Delvac 1™ Transmission Fluid 75W-80

Extra high performance synthetic blend manual transmission lubricant

- Engineered for the latest European heavy duty manual transmissions used in on highway commercial vehicles suitable for applications where severe low temperatures are found
- Designed using select base oils and an advanced additive package that enhances shifting performance, low temperature fluidity, and high temperature viscosity retention
- Formulated with extended performance reserve for applications requiring API GL-4 service

Mobil Delvac 1™ Gear Oil 75W-90

Fully synthetic rear axle lubricant

- For vehicles operating in severe service conditions
- Provides protection against thermal degradation and oxidation, reduced wear and corrosion
- Incorporates the latest technology in synthetic basestocks and advanced additives providing significant advantages over mineral gear oils

ExxonMobil

ExxonMobil Petroleum & Chemical BVBA

Hermeslaan 2
1831 Machelen
Belgium

©2015 Exxon Mobil Corporation
The Mobil Delvac and ExxonMobil logotypes are registered trademarks of Exxon Mobil Corporation or one of its subsidiaries.
The term "ExxonMobil" is used for convenience only and could refer to Exxon Mobil Corporation or one of its affiliates as the case may be.
Other logotypes and trademarks are the property of the respective owners.

Product information correct at the time of publication.

© Renault Trucks SAS all rights reserved

For more information visit us at www.mobil-delvac.com